



MKY20P



Output Ratings

Generating Set Model	Prime	Standby
230 / 400V, 50Hz	20 kVA / 16 kW	22 kVA / 18 kW
270 / 480V, 60Hz	24 kVA / 19 kW	27 kVA / 21 kW

Ratings at 0.8 power factor

Prime Rating

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Standby Rating

These ratings are applicable for supplying continuous power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3).

Ratings and Performance Data

Engine Make:	YORC
Engine Model:	A/4G42D4
Alternator Make:	YORC
Alternator Model:	YORC184E
Control Panel Make:	COMAP
Control Panel Model:	MK 7 / MK8
Circuit Breaker Make:	ABB
Circuit Breaker Type:	3 Pole MCCB
Base Frame:	Heavy Duty Fabricated Steel
Fuel Tank Capacity:	99 Litres
Engine Speed: RPM	1500
Frequency:	50Hz
Fuel Consumption:	Litres / Hours
Prime Rating	50% 2.7
	75% 3.9

Dimensions and Weights (Basic Genset)

L (mm)	W (mm)	H (mm)	Weight (kg)
1506	736	1100	510

Soundproof

Mikano Soundproof enclosure range ensures optimum performance in the harshest environments, they are fully weatherproof and incorporate internally mounted exhaust silencers. Designed on modular principles, they have interchangeable components permitting on-site repair, fully access doors and access panels that provide optimal service and maintenance access.

Extremely durable and robust, the enclosures are designed to resist corrosion and handling damage with the ability to withstand rough handling common on many construction sites.

The sound attenuated enclosures reduced sound levels to comply with the international and European standards.

Durable and Robust Construction

- High grade steel protected by powder coated paint.
- Single piece roof structure.
- Black finish stainless steel locks and hinges.
- Zinc plated / stainless steel fasteners.

Security and Safety

- Emergency stop push button mounted on enclosure.
- Cooling fan and battery charging alternator fully guarded.
- Fuel fill and battery can only be reached via lockable access doors.
- Exhaust silencing system totally enclosed for operator safety.

Excellent Service and Maintenance Access

- Side hinged doors on both sides of the enclosure opening to 180°
- Removable front and rear access panels.
- Oil drain piped to baseframe, exterior to the enclosure.

Transportability

- Tested and certified single point lifting facility.
- Drag points on baseframe facilitating handling from both sides.
- Base feet to aid forklift handling.

Dimensions and Weights (SoundProof)

L (mm)	W (mm)	H (mm)	Weight (kg)
2006	935	1230	740

General Information

Documentation

A full of operation and maintenance manuals and circuit wiring diagrams.

Generating Set Standards

The equipment meets the following standards: Bs5000, ISO 8528, ISO 3046, IEC 60034, NEMA MG- 1.22.



Warranty:

The products are warrantee against defects in material and workmanship for a period of 3500 hours or 4 years whichever comes first from the date of delivery to first user taking into consideration:

- Ensuring initial startup is performed by an authorized representative of the company (MIKANO International Limited) or its dealers.
- Installing, operating and maintaining the generator set in accordance with the manufacturer's instructions.

Email: info@mikano-intl.com, customercare@yorcpower.com

Website: www.mikano-intl.com, www.yorcpower.com